

AB-43JNE AB SERIES

ARTICULATING BOOM LIFTS



STANDARD FEATURES

- ▶ AC electric drive
- ▶ Proportional controls
- ▶ Load sensing system
- ▶ All motion alarm
- ▶ Active tilt alarm
- ▶ Battery charge display
- ▶ 60 A battery charger
- ▶ Non-marking tires
- ▶ 28mph wind rating
- ▶ Drive at full height
- ▶ Outside/inside rated
- ▶ CAN communication protocol
- ▶ Hour meter
- ▶ Turntable rotation lock
- ▶ Lifting points
- ▶ Horn
- ▶ Electric brakes
- ▶ Emergency lowering system
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

- ▶ ANSI A92.20

PRELIMINARY BROCHURE
SUBJECT TO CHANGE

AB-43JNE

AB SERIES

ARTICULATING BOOM LIFT

DIMENSIONS

Working Height (2 Person Indoor/1 Person Outdoor)	48.7 ft	15 m
Platform Height (2 Person Indoor/1 Person Outdoor)	42.7 ft	13 m
Up and Over Height	21.5 ft	6.55 m
Horizontal Reach	28.4 ft	8.65 m
A Length	22.1 ft	6.75 m
B Width	5 ft	1.52 m
C Stowed Height	6.9 ft	2.1 m
D Transport Height	9.8 ft	3 m
E Jib Length		
F Transport Length		
G Wheelbase	78.7 in	2 m
H Ground Clearance	8.3 in	0.21 m
I Platform Width	51.2 in	1.3 m
J Platform Length	35.4 in	0.9 m

SPECIFICATIONS

Rated Occupancy (Indoor/Outdoor)	2/1
Platform Capacity	507 lbs 230 kg
Turn Radius (Inside/Outside)	67/146 in 1.7/3.7 m
Gradeability	25%
Horizontal Platform Rotation	180°
Turntable Rotation	355° noncontinuous
Drive Speed Elevated	0.5 mph 0.8 km/h
Drive Speed Lowered	2.8 mph 4.5 km/h
Tires	22.4 x 9 in 57 x 23 cm
Weight	15,873 lbs 7,200 kg

POWER

Battery	48V/400 Ah
Hydraulic Tank	7.9 gal 30 L

